



## Crystalclear Enterprises.

Brochure on pumps CC2527/2528/2529/2530.



These Pumps use an advanced technology with high efficiency and minimised noise levels. The pumps are designed and manufactured according to all the requirements set by CE/GS/SAA/VDE. The pumps are IPX5 approved. The pump casing is made of reinforced plastic. The strainer includes a big filter basket, a see-thru cover for quick inspection of the strainer.




### APPLICATIONS

- Small size above ground pools of all types (including in-floor cleaning systems, solar heating systems, water features and water gardens etc).

### FEATURES

- Easy thread design makes strainer cover removal easy.
- See-Thru Strainer cover lets you see when the basket requires cleaning.
- Special PVC Connectors (1.5"/50mm) for quick connect.
- All components moulded of corrosion-proof reinforced thermoplastic for extra durability and long life.
- Service-ease design drain plug for easy maintenance in winter.
- The use of Mechanical seals (made of Carborundum & Graphite) to lengthen the life and lower the noise.
- Motor shaft is of Stainless Steel grade 304.

### Pump Performance Curve



**Pump and Pipe work connectors.**



**Technical's.**

Pump Model	CC2527	CC2528	CC2529	CC2530
in-put power Kw	0.55	0.6	1	1.1
Horse Power	1/2	3/4	1	1.1
Max. Head	7.5m	8m	10m	11m
Q. Max ltr per min	240L	265L	280L	296L
Approx M <sup>3</sup> per hour	14.4	15.9	16.8	17.76
Pump can be placed below water line of pool but needs a check (one-way) valve "if" placed above water line between pump and pool/pond.	Yes	Yes	Yes	Yes
Can be used with salt water as long as it is left on 24/7 and if turned off, "O" rings etc must be cleaned with copious amounts of fresh water after switch off so as not to allow the salt to dry on "O" Rings etc. (Warranty void if salt is found to be cause of fault).	Yes	Yes	Yes	Yes
Voltage	220-240	220-240	220-240	220-240
Hz	50	50	50	50
IP	IPX5	IPX5	IPX5	IPX5

Model	H.P.	Voltage	Hertz	Amps	Pipe Connection Size	Dimension L x W x H (cms)	Weight Kg(lbs)
CC2527	0.5	220-240	50	2.5	1.5"/50mm	52 x 18.5 x 25	8.8(19.4)
CC2528	0.75	220-240	50	2.6	1.5"/50mm	52 x 18.5 x 25	10(22)
CC2529	1.0	220-240	50	4.5	1.5"/50mm	56 x 19 x 30	12(26.4)
CC2530	1.5	220-240	50	5	1.5"/50mm	56 x 19 x 30	13.7(30.2)

All Specification are supplied by the manufacturer and are supplied by us on a good faith basis.

**Warranty: -**

**Products carry a 12 month warranty against the supply of faulty workmanship and/or goods when used under normal operation.**

- If the product becomes faulty within 14 days of receipt, we will ship a replacement item to the customer; after return of the original item so we can confirm the fault. We will also cover the shipment of the original item to us up to the value of £9.99 (a copy of the shipping receipt will be required) after we have confirmed the fault.
- After 14 days and within the 12 month warranty period, of receipt, if the product acquires a fault, then the customer will pay for the return shipping of the original product, so we can determine the fault. Once the fault is determined then we will send a replacement item (as long as it is in stock, a refund will be given if not) out to the customer, the shipping of which we will pay for.
  - Liability is strictly limited to the cost of a replacement item or full refund of faulty item.

\*\*The customer's statutory rights are not affected and these are **in addition** to those rights. \*\*

